DOWNLIGHT O SERIES LED
VOL.5

11610

FEATURES

LED ダウンライト(O6シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Reflector

ホワイトカラーの表面処理. (UGR<28)




Product ordering number **11610W-827H-020-075**
11610W-830H-020-075
11610W-840H-020-075

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø175 X H128
WEIGHT	Kg	0.85
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	20 (with power supply unit)
OUTPUT POWER	W	17
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	2,210
LOR	-	0.63
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	75
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
ON/OFF	80002	
1-10 Dimming	81001	
DALI Dimming	82001	
ON/OFF	80025	JAPAN
PWM Dimming	84002	JAPAN
DALI Dimming	82021	JAPAN
Triac Dimming	83011	AC 100~120V
Triac Dimming	83014	AC 220~240V

ALTO


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT O SERIES LED


11610

PHOTOMETRIC DATA


UGR =23.9








DRAWING DATA



INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr