DOWNLIGHT O SERIES LED
VOL.5

11315

FEATURES


LEDピンホール(Pinhole) adjustable タイプ (O3シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Optic

ビーム角20°, 30°, 40°が可能.




Product ordering number **11315W-827C-012-040**
11315W-830C-012-040
11315W-840C-012-040

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø96 X H83
WEIGHT	Kg	0.5
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	12 (with power supply unit)
OUTPUT POWER	W	10
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	1,350
LOR	-	0.48
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	40
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS




INDEX	ORDER NUMBER	NOTE
ON/OFF	80037	
1-10 Dimming	81026	
DALI Dimming	82047	
ON/OFF	80040	JAPAN
PWM Dimming	84014	JAPAN
DALI Dimming	82039	JAPAN


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT O SERIES LED

11315


PHOTOMETRIC DATA









DRAWING DATA











Ø85
W 0.50Kg


INSTALLATION INSTRUCTIONS











NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr