DOWNLIGHT OM SERIES LED
VOL.5

11542

FEATURES

Recessed LED double multi spot system (OM5 シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Reflector

NGR(ノングレアレフレクター)技術を適用し
た視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.
防塵とスクラッチ防止処理技術適用.

Optic

20° 又は 30° 配光角が可能.




Product ordering number **11542W-827H-060-030**
11542W-830H-060-030
11542W-840H-060-030

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	W173 X L329 X H132
WEIGHT	Kg	2.8
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	64 (with power supply unit)
OUTPUT POWER	W	54
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	5,900
LOR	-	0.87
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	30
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
1-10 Dimming	81019	2 Drivers
DALI Dimming	82028	
DALI Dimming	82025	JAPAN
DMX Dimming	85004	


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT OM SERIES LED

11542


PHOTOMETRIC DATA

m	30° Ø(m)	lux(center/side)
1	0.58	7308/3564
2	1.16	1827/891
3	1.74	812/396
4	2.32	457/223
5	2.90	292/143
6	3.48	203/99






DRAWING DATA



INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr