DOWNLIGHT OM SERIES LED
VOL.5

11543

FEATURES

Recessed LED triple multi spot system (OM5 シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Reflector

NGR(ノングレアレフレクター)技術を適用し
た視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.
防塵とスクラッチ防止処理技術適用.

Optic

20° 又は 30° 配光角が可能.




Product ordering number **11543W-827H-090-020**
11543W-830H-090-020
11543W-840H-090-020

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	W173 X L484 X H132
WEIGHT	Kg	4.0
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	96 (with power supply unit)
OUTPUT POWER	W	81
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	8,850
LOR	-	0.88
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	20
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
ON/OFF	80004	
1-10 Dimming	81005	
DALI Dimming	82003	
ON/OFF	80028	JAPAN
PWM Dimming	84007	JAPAN
DALI Dimming	82019	JAPAN
Triac Dimming	83013	AC 100~120V
Triac Dimming	83016	AC 220~240V

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT OM SERIES LED


11543

PHOTOMETRIC DATA


20°


m	Ø(m)	lux(center/side)
1	0.41	11387/5953
2	0.82	2847/1488
3	1.23	1265/661
4	1.64	712/372
5	2.05	455/238
6	2.46	316/165






DRAWING DATA








160X470

W 4.00Kg

INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr