DOWNLIGHT O SERIES LED
VOL.5

H11102

FEATURES

O1 High Performance シリーズ. LED wallwasher.

Housing

小型サイズ及び高出力エンジン技術の適用と強力な放熱性能実現.

Reflector

NGR(ノングレアレフレクター)技術を適用し
たウォールワッシング光学機能具現.
防塵とスクラッチ防止処理をしたリフレクター.

Trim

38mmサイズの選択が可能.




Product ordering number **H11102C-827C-007-WW**
H11102C-830C-007-WW
H11102C-840C-007-WW

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø33 X H94
WEIGHT	Kg	0.1
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	7.5 (with power supply unit)
OUTPUT POWER	W	6
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	800
LOR	-	0.23
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	Wallwasher
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS




INDEX	ORDER NUMBER	NOTE
ON/OFF	80021	Ø26 X 98(mm)
1-10 Dimming	81010	Ø26 X 160(mm)
ON/OFF	80031	JAPAN
PWM Dimming	84003	JAPAN

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT O SERIES LED


H11102

PHOTOMETRIC DATA




Q'TY: 3 /Luminaire spacing: 1.2m
Distance from the wall: 0.9m






DRAWING DATA



INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr