11571

FEATURES

Slot mounted LED single multi spot system (OM5 シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Trim Color

ホワイトオプション


Reflector

NGR(ノングレアレフレクター)技術を適用した視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.

防塵とスクラッチ防止処理技術適用.

Optic

20° 又は 30° 配光角が可能.




Product ordering number **11571B-827H-015-030**
11571B-830H-015-030
11571B-840H-015-030

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	W150 X L155 X H137
WEIGHT	Kg	1.05
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	16 (with power supply unit)
OUTPUT POWER	W	13
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	1,550
LOR	-	0.84
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	30
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
ON/OFF	80002	
1-10 Dimming	81001	
DALI Dimming	82001	
ON/OFF	80025	JAPAN
PWM Dimming	84001	JAPAN
DALI Dimming	82021	JAPAN
Triac Dimming	83010	AC 100~120V
Triac Dimming	83008	AC 220~240V

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT OM SERIES LED


11571

PHOTOMETRIC DATA


30°

m	Ø(m)	lux(center/side)
1	0.58	3751/1811
2	1.15	938/453
3	1.73	417/201








DRAWING DATA




INSTALLATION INSTRUCTIONS









NOTES

Attention Read carefully before installing.

The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.

The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr