DOWNLIGHT O SERIES LED
VOL.5

H11212

FEATURES

O2 High Performance シリーズ. LED wallwasher.

Housing

小型サイズ高出力放熱エンジン技術とアルミニウム加工技法を適用した放熱システム実現.

Reflector

NGR(ノングレアレフレクター)技術を適用したウォールワッシング光学機能具現.

防塵とスクラッチ防止処理技術適用.




Product ordering number **H11212C-827C-015-WW**
H11212C-830C-015-WW
H11212C-840C-015-WW

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø70 X H127
WEIGHT	Kg	0.29
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	14 (with power supply unit)
OUTPUT POWER	W	12.5
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	1,395
LOR	-	0.47
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	Wallwasher
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS




INDEX	ORDER NUMBER	NOTE
ON/OFF	80037	
1-10 Dimming	81025	
DALI Dimming	82035	
ON/OFF	80040	JAPAN
PWM Dimming	84014	JAPAN
DALI Dimming	82039	JAPAN

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT O SERIES LED


H11212

PHOTOMETRIC DATA




Q'TY: 3 /Luminaire spacing: 1.2m
Distance from the wall: 0.9m






DRAWING DATA



INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr