DOWNLIGHT O SERIES LED
VOL.5

# H11152

## FEATURES

O1.5 High Performance Series, Recessed LED Wallwasher.


**Housing**

小型サイズ及び高出力エンジン技術の適用と強力な放熱性能実現.

**Reflector**

NGR(ノングレアレフレクター)技術を適用したウォールワッシング光学機能具現.

防塵とスクラッチ防止処理技術適用.




Product ordering number **H11152C-827C-010-WW**
**H11152C-830C-010-WW**
**H11152C-840C-010-WW**

## SPECIFICATIONS

| INDEX | | DATA |
|---|---|---|
| DIMENSION | mm | Ø50 X H117 |
| WEIGHT | Kg | 0.15 |
| OPERATING VOLTAGE | V | AC 100~240V |
| POWER CONSUMPTION | W | 10 (with power supply unit) |
| OUTPUT POWER | W | 8.5 |
| COLOR TEMPERATURE | K | 2700 / 3000 / 4000 |
| LUMINOUS FLUX | lm | 1,170 |
| LOR | - | 0.33 |
| COLOR RENDERING INDEX | Ra | Over 80 |
| BEAM ANGLE | ° | Wallwasher |
| IP RATING | - | 20 |
| STORAGE HUMIDITY | % | 20% ~ 70% |
| STORAGE TEMPERATURE | ˚C | -40˚C ~ +50˚C |
| OPERATING TEMPERATURE | ˚C | -20˚C ~ +50˚C |

## SMPS




| INDEX | ORDER NUMBER | NOTE |
|---|---|---|
| ON/OFF | 80022 | Ø26 X 98(mm) |
| 1-10 Dimming | 81011 | Ø26 X 160(mm) |
| ON/OFF | 80033 | JAPAN |
| PWM Dimming | 84004 | JAPAN |


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT O SERIES LED

# H11152

## PHOTOMETRIC DATA








Q'TY: 3 /Luminaire spacing: 1.2m
Distance from the wall: 0.9m

## DRAWING DATA




## INSTALLATION INSTRUCTIONS




## NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr