DOWNLIGHT O SERIES LED
VOL.5

H11151

FEATURES

O1.5 High Performance シリーズ. LED directional.

Housing

小型サイズ及び高出力エンジン技術の適用と強力な放熱性能実現.

Reflector

NGR(ノングレアレフレクター)技術を適用した視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.

(Black NGR Finshing選択可能)

防塵とスクラッチ防止処理技術適用.


Optic

狭い角度から広い角度まで投光可能な多様なOptic構成及び小型サイズに高出力機能実現.

Tunable Temperature

CRI 80 2700K ~ 5000K (Standard)

CRI 90 2700K ~ 6500K (Option)



Product ordering number **H11151B-8TC-010-040**

SPECIFICATIONS

INDEX		DATA	
DIMENSION	mm	Ø50 X H114	
WEIGHT	Kg	0.15	
OPERATING VOLTAGE	V	AC 120~250V	
POWER CONSUMPTION	W	10	10
OUTPUT POWER	W	8.5	8.5
COLOR TEMPERATURE	K	2700	5000
LUMINOUS FLUX	lm	920	1,000
LOR	-	0.38	0.38
COLOR RENDERING INDEX	Ra	Over 80	
BEAM ANGLE	˚	40	
IP RATING	-	20	
STORAGE HUMIDITY	%	20% ~ 70%	
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C	
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C	

SMPS



INDEX		DATA
DIMENSION	mm	W30.5 X L280.5 X H21.5
OPERATING VOLTAGE	V	DC 8~14V Constant Current
DIMMING INTERFACE	-	DALI DT8
IP	-	20

This product can be changed according to the client.(location)


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

DOWNLIGHT O SERIES LED


H11151

PHOTOMETRIC DATA


2700K



5000K



DRAWING DATA



NOTES


Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

DOWNLIGHT O SERIES LED


H11151

INSTALLATION INSTRUCTIONS



WIRING DIAGRAMS

* Must install SMPS in separate control box (SMPS size does not fit into the cut-out hole)
Parallel electrical wiring (Max connection of 7 fixtures)
Maximum run length (from SMPS DC connecting point to last fixture) : Max 8M (using AWG18 cable)



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr