# 11612

## FEATURES

LED Wallwasher タイプ (O6シリーズ)

**Housing**

一体型ボディ構造で強力な放熱性能を実現.

**Reflector**


NGR(ノングレアレフレクター)技術を適用した視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.

防塵とスクラッチ防止処理技術適用.

**Tunable Temperature**

CRI 80 2700K ~ 5000K (Standard)

CRI 90 2700K ~ 6500K (Option)



Product ordering number **11602C-8TH-020-WW**

## SPECIFICATIONS

| INDEX | | DATA | |
|---|---|---|---|
| DIMENSION | mm | Ø175 X H120 | |
| WEIGHT | Kg | 0.9 | |
| OPERATING VOLTAGE | V | AC 100~240V | |
| POWER CONSUMPTION | W | 20 | 20 |
| OUTPUT POWER | W | 18 | 18 |
| COLOR TEMPERATURE | K | 2700 | 5000 |
| LUMINOUS FLUX | lm | 1580 | 1770 |
| LOR | - | 0.4 | |
| COLOR RENDERING INDEX | Ra | Over 80 | |
| BEAM ANGLE | ° | Wall Washer | |
| IP RATING | - | 20 | |
| STORAGE HUMIDITY | % | 20% ~ 70% | |
| STORAGE TEMPERATURE | ˚C | -40˚C ~ +50˚C | |
| OPERATING TEMPERATURE | ˚C | -20˚C ~ +50˚C | |

## SMPS



| INDEX | | DATA |
|---|---|---|
| DIMENSION | mm | W76 X L130 X H30 |
| OPERATING VOLTAGE | V | DC 32~40V Constant Current |
| DIMMING INTERFACE | - | DALI DT8 |
| IP | - | 20 |


This product can be changed according to the client.(location)

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


# 11612


## PHOTOMETRIC DATA

### 2700K





Q'TY: 3 /Luminaire spacing: 1.2m / Distance from the wall: 0.9








### 5000K





Q'TY: 3 /Luminaire spacing: 1.2m / Distance from the wall: 0.9



## DRAWING DATA




## NOTES


Attention Read carefully before installing.

The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.

The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

## INSTALLATION INSTRUCTIONS




## NOTES

Attention Read carefully before installing.

The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.

The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr

H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea

Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr